

## Re: subreport and null value problem

**Source:** <http://www.tech-archive.net/Archive/Access/microsoft.public.access.reports/2004-04/1878.html>

---

**From:** Marshall Barton ([marshbarton\\_at\\_wowway.com](mailto:marshbarton_at_wowway.com))

**Date:** 04/28/04

Date: Wed, 28 Apr 2004 13:36:10 -0500

tony wrote:

>I tried your suggestion below, but am a little confused  
>about the label control. When I go to the properties  
>dialog box for the label, there are no places to enter  
>events or control source. Where should I place the code  
>  
>Me.thelabel.Visible = Not Me.subreport.Report.HasData  
>  
>and/or how do I attach that code to the label?

Sorry, I should have said that the code needs to be in the  
Format event of the **\*\*section\*\*** containing the subreport.

The code is not "attached" to the label, it just operates on  
the label.

```
--
Marsh
MVP [MS Access]
>>-----Original Message-----
>>Tony wrote:
>>
>>>I am having the problem: I have a "Count(*)" function
>in
>>>the footer of a report, and within the function I've
>>>included the "Nz[field],0" operator to show the 0 when
>no
>>>records are present. When the report is viewed stand-
>>>alone, it prints out fine. However, when it is included
>>>as a subreport in another main report, it disappears
>when
>>>the value is 0. How can I get that subreport to show up
>>>even if the value is 0?
>>
>>
>Marshall BArton wrote
>>A subreport with no records does not have any values, not
>>even Null. You can, however test if the subreport has
>data
>>or not and use that to make a control on the main report
>>visible of not. For example, if you have a label control
>>with the caption 0 on the main report in the same place as
>>the subreport control, then you can use a line of code:
```

microsoft.public.access.reports: Re: subreport and null value problem

```
>>  
>>     Me.thelabel.Visible = Not  
>Me.subreport.Report.HasData  
>>  
>>to display the zero when there is nothing in the  
>subreport.
```