

# Re: copy of email

---

*Source:*

<http://www.tech-archive.net/Archive/Development/microsoft.public.win32.programmer.messaging/2006-05/msg0011>

---

- *From:* "Dmitry Streblechenko" <[dmitry@xxxxxxxxxxxx](mailto:dmitry@xxxxxxxxxxxx)>
  - *Date:* Thu, 25 May 2006 11:28:18 -0700
- 

2. PR\_SENTMAIL\_ENTRYID is set on the message itself. OnWriteComplete will work for sure.
3. You get the complete message in OnWriteComplete. You can create your own named prop tag using IMessage::GetIDsFromNames, then set it using IMessage::SetProp or HrGetProp.

Dmitry Streblechenko (MVP)  
<http://www.dimastr.com/>  
OutlookSpy – Outlook, CDO  
and MAPI Developer Tool

"Reesh" <[Reesh@xxxxxxxxxxxxxxxxxxxxxxxxxxxx](mailto:Reesh@xxxxxxxxxxxxxxxxxxxxxxxxxxxx)> wrote in message  
[news:F3E83521-C1B9-4EE7-A82A-2B5FB69C455E@xxxxxxxxxxxxxxxxxxxx](mailto:news:F3E83521-C1B9-4EE7-A82A-2B5FB69C455E@xxxxxxxxxxxxxxxxxxxx)

## 2. Why not simply set the PR\_SENTMAIL\_ENTRYID

Where do I set the PR\_SENTMAIL\_ENTRYID?  
(i mean in which event, OnCheck/OnSubmit/OnWrite...)

```
HrGetOneProp(???/*msgstore/msg/folder*/,PR_SENTMAIL_ENTRYID,&setsentmail);  
HrSetOneProp(myfolder,&setsentmail);
```

3. OnSubmit/OnWrite/OnWriteComplete/OnSubmit sequence fires only once for each outgoing message, but OnWrite/OnWriteComplete also fires for the message being forwarded/replied since Outlook updates icon and PR\_LAST\_VERB\_xxx properties.

How can I differentiate OnWrite and OnWriteComplete methods fired for updating "icons and PR\_LAST\_VERB\_xxxx" or "outgoingmessage"?

I can get outgoing message always if it fired for updating "icon and PR\_LAST\_VERB\_xxx".

Re: copy of email

In Which method, I can get the complete message?

How can I get the info. abt outgoing e-mails are saved in sent items folder or not?

Set your own named property when OnSubmit is called then check for that property in OnWriteComplete to see if you have the eright message.

How can I set my own named property to copy to outgoing e-mails?

Thanks in advance.

Regards,  
Reesh.

Dmitry Streblechenko (MVP)  
<http://www.dimastr.com/>  
OutlookSpy – Outlook, CDO  
and MAPI Developer Tool

"Reesh" <Reesh@xxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message  
[news:4966C501-D77C-4AA9-8527-35C5684F04BD@xxxxxxxxxxxxxxxxxxxx](mailto:news:4966C501-D77C-4AA9-8527-35C5684F04BD@xxxxxxxxxxxxxxxxxxxx)

Thank you for your response.

Q: How can I take a copy of outgoing e-mail in .msg format from outlook using ece?  
(i mean i have to take a copy of an outgoing e-mail into "xxx" mapi folder like sent items. but it's not sent items folder.)  
Note: forwarded mails also.

OnSumbit and OnWrite are fires morethan one time for forwarded messages.  
How do I solve this problem?

Regards,  
--  
Reesh

Re: copy of email

"Dmitry Streblechenko" wrote:

I am not sure what what your question is...  
Are you trying to retrieve  
the  
sender properties when a message is being  
sent?  
OnSubmit/OnWrite callbacks fire before the  
message is handed to a  
spooler/transport provider, which sets the  
sender related properties.  
The earliest you can access these properties  
is when the message is  
moved  
to  
the Sent Items folder. You can set up and  
advise sink on tehe SEnt  
Items  
folder contact table to get notified when a  
new message is created  
there.

Dmitry Streblechenko (MVP)  
<http://www.dimastr.com/>  
OutlookSpy – Outlook, CDO  
and MAPI Developer Tool

"Reesh"

<Reesh@xxxxxxxxxxxxxxxxxxxxxxxxxxxx>

wrote in message

<news:C234B790-C527-4665-9B23-821E9D2DA56E@xxxxxxxxxxxxxxxxxxxx>

I overridden  
OnWriteComplete method  
of IExchExtMessageEvents.  
I  
created  
new  
empty message under "xxx"  
mapi folder then "CopyTo"  
,"SaveChanges"  
of  
new  
msg  
and updated  
PR\_MESSAGE\_FLAGS  
property on new msg. I got  
Outgoing  
mail  
properties except

Re: copy of email

sendermailaddress. How do  
I get a copy of outgoing  
mail  
in  
Outlook using ece?

Thanks in advance.

Regards,

--

Reesh