

Re: Siemens TAPI 120 – CSTA

Source:

<http://www.tech-archive.net/Archive/Development/microsoft.public.win32.programmer.tapi/2005-10/msg00016.html>

- *From:* "Andreas Marschall [MVP TAPI]" <Andreas.Marschall@xxxxxxxxxx>
 - *Date:* Sun, 2 Oct 2005 08:29:24 -0700
-

"Hazem K" <HazemK@xxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message <news:3A43A696-39D7-46DD-AEC0-4255AE717397@xxxxxxxxxxxxxxxxxxxx>

- >> What exactly fails how?
- > I tried installing it couple of days ago for 3 time, and in all times I
- > got
- > errors while some database files were updated (or so..), and after that a
- > big
- > number of failures and error messages popued, and all of the PC system
- > became somewho unstable so I restored it to a restore point.
- >
- > anyways I just tried for another time –to get the error messages again–
- > and
- > this time everything went smooth till the end (!), then it displayed an
- > error
- > message of :
- > "Service could not be started. CCMCService" with no other errors

Hazem,
the CCMCService is only intended for HiPath AllServe systems and requires additional HiPath services, therefore it can't start.
Please unistall HT170 completely and install with other setup settings.
(Being on abusiness trip I currently have the setup available to tell the exact settings.)
Please select custom configuration and install only the minimum configuration.

- > After a windows restart, a fax program using an internal modem couldnt
- > ititalize its TAPI modem, then "Phone and modem options" from control
- > panel
- > could not be opened anymore with an error message:
- > "Phone and modem control panel can not be opened You may have a problem
- > starting telephony service", so I uninstalled the 170 tsp again.

O.k.,these issues are all caused by selecting the setup configuration containing CCMC.

Re: Siemens TAPI 120 – CSTA

- >> HT120 via CMD (CMD can use a COM port).
- >
- > I installed HT120 and CMD on my WinXP machine, connected the CSTA cable to
- > my com1 serial port and to the pbx..
- >
- > Configured TAPI120 As folowing:
- > System: CMD
- > CallNumber: 11 (this is thu number I use to dial the extention)
- > Name: myTAPI 120
- > IP address: 127.0.0.1
- > IPPort: 8001 (default,