

Re: Help: Login failed for User ???

Source:

<http://www.tech-archive.net/Archive/DotNet/microsoft.public.dotnet.framework.adonet/2006-04/msg00092.html>

- *From:* "Jim Hughes" <NOSPAMJ3033@xxxxxxxxxxxx>
 - *Date:* Tue, 4 Apr 2006 09:34:44 -0700
-

The users desktop permissions are not relevant to their ability to access the SQL Server. They will not need to be admins on their desktop or the server.

UserID and Passwd are not used in the connection string when trusted/integrated security is used and should not be present.

You can test database access by creating an empty file with as UDL extension and then opening it and setting the parameters and using the Test Connection button.

The SQL Server will need to be a member server of the domain as will the users workstations.

Internal DNS will need to be properly configured with appropriate records to access the domain controllers.

Firewall settings on the SQL Server will need to be set to allow access for Named Pipes.

The SQL Server Network Configuration network utility will need to be set to allow Network connections via Named Pipes and perhaps TCP/IP.

"Michael" <Michael@xxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message news:856C5ED8-F4EE-4F45-934D-18752E11A7EE@xxxxxxxxxxxxxxxxxxxx

Hi Jim,

I tried using the new version of the connect string and have the same problem. I'll include more detail here:

Here is some additional info that might help. I have the following setup in

Enterprise Manager.

Server -> Security -> Logins -> General Tab

The name is listed as 'NARCO?????\christian.gaut

The properties for this user are set as:

Windows Authentication

Domain = NARCO????? (but grayed out)

Security Access = Grant

Re: Help: Login failed for User ???

and the default database is set.

Server Role Tab:

Nothing set here.

Database Access:

Only the database that needs accessing is checked for permission.

Now if I look in the following

Database -> Users (Users for this database)

The name is christian.gaut and the Login Name value includes the domain
and

has Permit access to db.

The properties are set as followed:

Permit in Database Role:

Public, db_owner, db_datareader, db_datawriter are checked.

and for the permissions I set every possible option (Select, insert,
update

and delete