Re: Backup service authentication question

Source:
http://www.tech−archive.net/Archive/Exchange/microsoft.public.exchange.admin/2007−03/msg00025.html

- *From*: Andy David {MVP} <adavid@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx>
- *Date*: Wed, 28 Feb 2007 20:19:28 −0500

On Wed, 28 Feb 2007 19:05:56 −0500, "Troy Bruder"
<troy_bruder@xxxxxxxxxxx> wrote:

> Hello,
>
> I have a fairly small Exchange 2003 installation. My HQ site has a single
> Exchange 2k3 BE server. The HQ site is connected to 3 other remote sites
> via a mesh network. Each of those sites has a local Exchange 2k3 BE server.
>
> I use BackupExec 11d for my backups. I recently noticed that if my Exchange
> server in the HQ site is unavailable, the Exchange backups in the remote
> sites fail in connecting to the resource.

Which resource?

> It appears like an authentication
> issue. When the main site comes back on line, backups can run again without
> issue.

When the Exchange server is unavailable? What causes that?

> Each site has at least one 2k3 domain controller as well as a local
> BackupExec media server. AD sites and services is properly setup and all
> authentication occurs locally without traversing the WAN.
>
> Can someone please explain this authentication "scenario" to me and if there
> is a way to configure it to prevent remote site backup issues when the HQ
> site is unavailable.
>
> Thanks!
> Troy

Do the backup servers share anything in common?
.