

Re: creating a new mailbox store.

Source:

<http://www.tech-archive.net/Archive/Exchange/microsoft.public.exchange2000.admin/2004-06/0268.html>

From: Jim Schwartz (*shamusnc_at_poc.earthlink.net*)

Date: 06/04/04

Date: Fri, 04 Jun 2004 02:55:02 GMT

I'd go with what is behind door a).

You really do need to follow up on the underlying cause. I think it's 99.99% of the time now Ben. ;-)

"Ben Winzenz [Exchange MVP]" <ben_winzenz@NOSPAMdotmessageonedotcom> wrote in message news:uR2ceWbSEHA.3968@TK2MSFTNGP09.phx.gbl...

> *If your database has been resurrected and is now in a consistent state with*

> *mailbox stores mounted, you can either*

> *a) simply "move" the mailboxes to a new mailbox store using the Exchange*

> *Tasks, move mailboxes, or*

> *b) use eseutil again with the /d option (defragment), which will, in*

> *essence, create a brand new copy of the store.*

>

> *Both options will work just as well, though using eseutil can take longer.*

> *Eseutil would require the store to be offline again, while the move mailbox*

> *function requires the store to be online. Also, have you determined the*

> *underlying cause of the corruption? 99% of the time, database corruption is*

> *caused by faulty hardware. If it is a hardware problem and you have not*

> *fixed it, the corruption will very likely occur again.*

>

> --

> *Ben Winzenz*

> *Exchange MVP*

> *"chrism" <chris@no_spam> wrote in message*

> *news:OjUtt3aSEHA.3692@TK2MSFTNGP10.phx.gbl...*

> > *We have Exch2000 Server and the only mailbox store has been corrupted.*

> > *We resurrected it with eseutil but I saw a document in the KB about*

> *creating*

> > *a new database and*

> > *blowing out the email to .pst and re-importing it back into the new*

> *mailbox*

> > *store.*

> >

microsoft.public.exchange2000.admin: Re: creating a new mailbox store.

> > *However, I can't find that document. Anybody able to locate it. Pls*

help

> > *!!*

> >

> > *thanks,*

> >

> > *chrism*

> >

> >

>

>