

Re: ISA2004 – multiple external interfaces

Source: <http://www.tech-archive.net/Archive/ISA/microsoft.public.isa/2005-04/msg00011.html>

- *From:* "A.Klimkin" <aklimkin at mail dot ru>
 - *Date:* Thu, 31 Mar 2005 09:34:44 +0400
-

> ... When looking at the listener config it allows for configuration of
> multiple external IPs – does it indeed only allow 1?

Yes, it allows to bind multiple IPs. But to the **single** interface. You cannot have more than one physical external interface. Also, if you bind multiple IPs to the external interface, you have no control over what particular IP address will be used as source address for outgoing traffic. This could lead you to the problems communicating to some hosts (e.g. mail relays) that use quite bogus authentication scheme by source IP address.

Regards,
Andrew

-
- *Follow-Ups:*
 - ◆ ***Re: ISA2004 – multiple external interfaces***
 - ◇ *From:* Trevor Miller
 - *References:*
 - ◆ ***Re: ISA2004 – multiple external interfaces***
 - ◇ *From:* Trevor Miller
 - Prev by Date: ***external user can't send mail thru isa2000***
 - Next by Date: ***Re: HTTP X FORWARDED FOR and ISA server 2004***
 - Previous by thread: ***Re: ISA2004 – multiple external interfaces***
 - Next by thread: ***Re: ISA2004 – multiple external interfaces***
 - Index(es):
 - ◆ ***Date***
 - ◆ ***Thread***