

## Re: Move messages back to queue from badmail folder

**Source:**

[http://www.tech-archive.net/Archive/Internet-Server/microsoft.public.inetserver.iis.smtp\\_nttp/2004-03/0232.html](http://www.tech-archive.net/Archive/Internet-Server/microsoft.public.inetserver.iis.smtp_nttp/2004-03/0232.html)

---

**From:** Gummy Mummy ([gummy\\_at\\_gummymummy.com](mailto:gummy_at_gummymummy.com))

**Date:** 03/24/04

Date: Tue, 23 Mar 2004 20:00:53 -0800

Thanks! That worked perfectly!

"m.marien" <mm AT RiverCityCanada DOT com> wrote in message  
news:10620975bausec4@corp.supernews.com...

>

> "Gummy Mummy" <[gummy@gummymummy.com](mailto:gummy@gummymummy.com)> wrote in message  
> news:1061nq0ma81ik63@news.supernews.com...

>> *Is there a way or a procedure to move messages back from the badmail to  
> the*

>> *queue folder?*

>> *We had some issues today and I really need to queue those badmail  
messages*

>> *back up.*

>> *IIS5 / W2K Server.*

>> *Thanks*

>>

> *I think the original message is placed in the /Inetpub/mailroot/badmail  
> folder with the extension of \*.BAD. There are two other files that have  
some*

> *error messages (\*.BDP/\*.BDR) in them. You can ignore them. Just move the  
> \*.BAD files to the pickup directory. The SMTP server will attempt to send  
> them again.*

>

> *Be careful about this operation, as the SMTP server will send the messages*

> *to all the valid recipients listed in the TO/CC and BCC fields. If the*

> *message originated from somewhere else, your SMTP server will try to send  
it*

> *again as if it originated from your server. In other words, you will be*

> *manually relaying any received messages.*

>

>