

Re: Backslash in "Default Domain" doesn't work

Source:

<http://www.tech-archive.net/Archive/Internet-Server/microsoft.public.inetserver.iis/2004-05/0556.html>

From: Egbert Nierop \ (MVP for IIS\) (*egbert_nierop_at_nospam.invalid*)

Date: 05/05/04

Date: Wed, 5 May 2004 21:31:04 +0200

"Kevin" <anonymous@discussions.microsoft.com> wrote in message
news:8acd01c432c5\$37dc3120\$a401280a@phx.gbl...

> *I've configured IIS to authenticate users against all*
> *trusting domains by putting a backslash in the "Default*
> *Domain" field in the "Authentication Methods" form per*
> *the instructions at*

Hi Kevin,

The MSDN docs specify this (see below)!

To get the effect that you want, you need to specify that domain by a configuration utility that automates creation websites. This utility should set that domain.

http://msdn.microsoft.com/library/default.asp?url=/library/en-us/iissdk/iis/ref_mb_defaultlogondomain.asp

In Web, FTP, and NNTP servers, the DefaultLogonDomain property is used to specify the default domain that the server uses to authenticate users (in a Web hosting scenario where UserIsolationMode = 2). If the value of DefaultLogonDomain is not specified, the default domain will be the domain name controlled by the computer, if the computer is a domain controller. If the computer is not a domain controller, the default domain will be the computer name.

In the case of FTP, IIS uses this domain name to query the corresponding Active Directory (AD) for the two properties required for each user in the Web hosting scenario: msIIS-FTPRoot and msIIS-FTPDir.