

Re: Ipaq 5915 Wireless Network Connection (FAILURE)

Source:

<http://www.tech-archive.net/Archive/PocketPC/microsoft.public.pocketpc.wireless/2007-01/msg00022.html>

- *From:* "Sven" <sejohannsen@xxxxxxxxxxx>
 - *Date:* Thu, 4 Jan 2007 22:41:15 -0700
-

Maybe I'm too late but why would you turn off the DHCP Server, or change any other device on the network? You just need to configure static entries on the PPC itself. That precludes it requesting addresses via DHCP.

That of course doesn't preclude bad key issues, but it precludes bad keys messing up getting the right IP, mask, gateway.

—

Sven

MVP – Mobile Devices

"David Hettel" <dah618@xxxxxxxxxxx> wrote in message
[news:eR0h\\$08LHHA.4912@xxxxxxxxxxxxxxxxxxxxxxxxxxxx](mailto:news:eR0h$08LHHA.4912@xxxxxxxxxxxxxxxxxxxxxxxxxxxx)

Yes you'll need to set (manually configure an IP address for the Belkin, and then turn off the DHCP Server of the Belkin not the DHCP client.) you'll need to manually enter the IP address for each computer as well as the DNS IP address, and the Default Gateway IP address and subnet mask.