

Re: SQL Server 2000 Profiler

Source:

<http://www.tech-archive.net/Archive/SQL-Server/microsoft.public.sqlserver.tools/2004-02/0252.html>

From: Jasper Smith (*jasper_smith9_at_hotmail.com*)

Date: 02/24/04

Date: Tue, 24 Feb 2004 18:36:17 -0000

You can load a trace file(.trc) or multiple if you've specified rollover into a table using the following syntax

```
select * into mytracetable
from ::fn_trace_gettable('c:\mytrace.trc', default)
```

--

HTH

Jasper Smith (SQL Server MVP)

I support PASS - the definitive, global community for SQL Server professionals -

<http://www.sqlpass.org>

"Kevin H" <anonymous@discussions.microsoft.com> wrote in message news:A7720F84-07A7-41BD-A52B-2110E10FD677@microsoft.com...

> Hi and thank you for your reply Jasper.

>

> So what I am taking from this is that this is an issue and there is not a way around it in profiler?!?

> I understand I could log it to a table but I dont want to do that because of other issues.

>

> Is there a sp_ procedure to load a trace file to a table? This way I could load it when I want or need to.

>

> Thanks,

> Kevin

>

> ----- Jasper Smith wrote: -----

>

> This is indeed an issue with Profiler filtering IIRC. What you can do is

> save the trace file and load it into a SQL table. Then you have much better

> filtering abilities using TSQL.

>

> --

> HTH

>

> Jasper Smith (SQL Server MVP)

>

> I support PASS - the definitive, global community for SQL Server professionals -

> <http://www.sqlpass.org>

>

microsoft.public.sqlserver.tools: Re: SQL Server 2000 Profiler

```
>
> "Kevin H" <anonymous@discussions.microsoft.com> wrote in message
> news:000101c3fa4f$1a706600$a001280a@phx.gbl...
> > Hi and thanks for your help all.
> > My problem is this:
> > I am running a trace on "Applicaiton name" like " SQL
> > Query Analyzer". The problem is that I am getting a result
> > set with a large number of rows with the "Application
> > name " as a blank. I am not wanting any row that does not
> > have only "SQL Query Analyzer". I do not want the rows
> > with blanks.
> >> I have tried with Not like "" and " " and still get the
> > same result set.
> >> Below is some of the examples I get with blank application
> >> names which I dont want in my results set.
> >>> Can someone help me ?
> >> Thanks,
> > Kevin H
> >> example:
> >> SQL:BatchStarting IF @@TRANCOUNT > 0 COMMIT TRAN
> > sa
> > 3044 86 2004-02-23 15:43:31.357
> > SQL:BatchStarting set implicit_transactions off
> > sa
> > 3044 86 2004-02-23 15:43:31.357
> > SQL:BatchStarting set implicit_transactions on
> > sa
> > 3044 86 2004-02-23 15:43:31.373
> > SQL:BatchStarting IF @@TRANCOUNT > 0 COMMIT TRAN
> > sa
> > 3044 86 2004-02-23 15:43:31.373
> > SQL:BatchStarting set implicit_transactions off
> > sa
> > 3044 86 2004-02-23 15:43:31.373
> >>
```