

Re: Run command arguments

Source:

<http://www.tech-archive.net/Archive/Scripting/microsoft.public.scripting.wsh/2005-05/msg00106.html>

- *From:* "McKirahan" <News@xxxxxxxxxxxxxx>
 - *Date:* Wed, 11 May 2005 23:45:54 -0500
-

"KAREN27" <KAREN27@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message
news:12C3F066-3208-475F-BAEC-3F6BF04C4F5A@xxxxxxxxxxxxxxxxxxxx

> Hi all,
>
> I'm using this code below so a particular user can change their screen
> saver settings easily.
>
> <job id="12345-WSH Script">
>
> <script language="JScript">
>
> var WshObj;
> WshObj = WScript.CreateObject("WScript.Shell");
> WshObj.Run("RunDll32.exe desk.cpl, InstallScreenSaver", 1, 1);
> </script>
>
> </job>
>
> All of this works OK, although I'm trying to determine what the argument
> "1,
> 1" on the end do.
>
> Also, what other numbers can I apply instead of these numbers, and what
> then
> will they do that's different?
>
> Thanks very much for your help
> Karen

Run Method

Description: Creates a new process that executes strCommand.

Syntax: object.Run (strCommand, [intWindowStyle], [bWaitOnReturn])

Download the WSH documentation:

<http://msdn.microsoft.com/scripting/>

- **References:**

- ◆ **Run command arguments**
 - ◇ From: KAREN27

- Prev by Date: **Run command arguments**
- Next by Date: **Hiding Drives**
- Previous by thread: **Run command arguments**
- Next by thread: **Hiding Drives**
- Index(es):
 - ◆ **Date**
 - ◆ **Thread**