

Re: Map network drive in background

Source:

<http://www.tech-archive.net/Archive/Win2000/microsoft.public.win2000.networking/2005-04/msg00687.html>

- *From:* "s" <s@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx>
 - *Date:* Fri, 22 Apr 2005 07:23:19 -0700
-

The application is running as a service, so when the server starts the service is automatically started, just as a normal service under windows. So the application is running before the user logs in.

"Pegasus (MVP)" wrote:

> Applications don't just "run" in the background – something's got
> to launch them. What's launching yours?
>
>
> "s" <s@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message
> news:DBD6F370-4974-4064-89A7-E33F2767D7F4@xxxxxxxxxxxxxxxxxxxx
>> first choice has already been implemented and doesn't work too well that's
> why
>> i;m trying to map a network drive
>>
>> how would i acheive second choice ? If application is running in
> background
>> when server has started will network drive be mapped with that process ?
>>
>> "Pegasus (MVP)" wrote:
>>
>>> You have two choices:
>>> – Use UNC coding, or
>>> – Map the drive with the same process that launches the application.
>>>
>>>
>>> "s" <s@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message
>>> news:5EBE75E8-C7EA-4851-933A-654828458F88@xxxxxxxxxxxxxxxxxxxx
>>>> Hi,
>>>>
>>>> I wanted to map the network drive so the application can see it
> without a
>>>> user logging on.
>>>>
>>>> "S" wrote:
>>>>
>>>>> I'm trying to get an application to see a share such as

Re: Map network drive in background

```
> \\server1\share
>>> as a
>>>>> drive letter g:\. I'm not an application developer, I'm from a
> server
>>> support
>>>>> background.
>>>>>
>>>>> Is there
```