

Re: Quarantine rqc parameter details

Source:

http://www.tech-archive.net/Archive/Win2000/microsoft.public.win2000.ras_routing/2004-04/0128.html

From: Ashok [MSFT] (ashnando_at_online.microsoft.com)

Date: 04/05/04

Date: Mon, 5 Apr 2004 10:04:19 +0530

You can find quarantine configuration details at

<http://www.microsoft.com/downloads/details.aspx?FamilyID=fe902704-52dd-4bbe-8a75-f8fbb76cd28a&displaylan>

Regarding the parameters that rqc takes: rqc <ConnName> <TunnelConnName>
<Port> <Domain> <Username> <String>

where

<ConnName >: Name of the dial-up connectiod

<TunnelConnName>: Name of the VPN connectiod.

As you are using tunnel connection, <ConnName> is NULL.

<Port >: Port number that rqs server is listening. [At server side it can be configured using registry entry:

"HKLM\system\CurrentControSet\Services\rqs\port"]

<String>: This is the shared secret key that client and server knows about.

(At server side this string can be configured using

"HKLM\system\CurrentControlSet\Services\rqs\AllowedSet".

You can call rqc with appropriate parameters using VB script.

--

Thanks

Ashok

ashnando@online.microsoft.com

This posting is provided "AS IS" with no warranties, and confers no rights.

"John Pickett" <jpickett@acs.utah.edu> wrote in message

news:%234B8TzNGEHA.3180@TK2MSFTNGP12.phx.gbl...

> Hello,

>

> I've been struggling to get the rqc component to correctly notify the rqs

> app a user has passed our quarantine control application. A sample call

> would look like this:

>

> rqc.exe NULL "VPN Access to domain" 7250 DOMAIN USERNAME Example1a

>

> where DOMAIN is really our domain and USERNAME is my testing username. I

> think I'm really close but there are two parts that are bugging me and I'm

> not sure how either relate to each other or which (possibly both?) are

> causing the script to fail.

>

microsoft.public.win2000.ras_routing: Re: Quarantine rqc parameter details

> The first uncertainty is regarding the first parameter that gets set to
NULL
> by the CM when it calls our system check application. The documentation
> calls this parameter the %DialRasEntry% and the rqc exe describes it as:
>
> ConnName: the name of the RAS connection on this host
>
> in the format:
>
> rqc <ConnName> <TunnelConnName> <Port> <Domain> <Username> <String>
>
> What exactly is this and why is CM setting it to NULL? Any ideas?
>
> The other part I'm not sure of is the version string at the end. In all
the
> examples it suggests putting the version of your script. I'm not sure if
> this means the CM script, my checking script, etc... The documentation
the
> rqc.exe file gives doesn't help any:
>
> String: the string to send
>
> GREAT :-) Does this string actually "check" against anything? Or is it
> basically any string whatsoever would work?
>
> Any help will be much appreciated. I've struggled with this for a long
time
> now. I thought writing the VB app to do the quarantine check would be
> hard.. This has been a huge road block.
>
> John P.
>
>