

# Re: How to Modify Backup Runner to type "Copy" mode

---

*Source:*

<http://www.tech-archive.net/Archive/Windows/microsoft.public.windows.server.sbs/2007-03/msg02232.html>

---

- *From:* "Merv Porter [SBS-MVP]" <[mwport@xxxxxxxxxxxxxxxxxxxxxx](mailto:mwport@xxxxxxxxxxxxxxxxxxxxxx)>
  - *Date:* Fri, 16 Mar 2007 09:07:34 -0400
- 

Not sure how to get around this. You may have to switch to just using the native NTbackup and not the SBS Backup Wizard.

--  
Merv Porter [SBS-MVP]

=====  
"DOTMED/PCRESQ" <[DOTMEDPCRESQ@xxxxxxxxxxxxxxxxxxxxxxxxxx](mailto:DOTMEDPCRESQ@xxxxxxxxxxxxxxxxxxxxxxxxxx)> wrote in message [news:54CD2F9A-5C9F-42B9-BA24-A7A1B251A209@xxxxxxxxxxxxxxxxxxxxx](mailto:news:54CD2F9A-5C9F-42B9-BA24-A7A1B251A209@xxxxxxxxxxxxxxxxxxxxx)

Hi Merv,

Did what you suggested and saved "type=copy" in backup job, but later scheduled run revealed it was still doing type "normal". (From Backup log details).

Appears that 'backuprunner' may be hard coded with command line parameters?

Where does it get it's parametres from? Registry hack? (where mode normal maybe = value 1, 'copy' = 2 ?) \*\* Just a suggestion !

Thanks,  
Neil Horley

"Merv Porter [SBS-MVP]" wrote:

Hi Neil,

While I've never had occassion to do this, I believe you can first run the SBS Backup Wizard, then open NTBackup | Backup tab | Load Selections and Browse/Select the .bks location (C:\Program Files\Microsoft Windows Small Business Server\Backup\Small Business Backup Script.bks). Then on the menu,

Re: How to Modify Backup Runner to type "Copy" mode

Tools | Options | Backup Type. Then change the type from Normal to Copy and save the .bks file.

--

Merv Porter [SBS-MVP]

=====

"DOTMED/PCRESQ"

<DOTMED/PCRESQ@xxxxxxxxxxxxxxxxxxxxxxxxxxxx> wrote in message

news:44346644-A33C-4FD3-B94A-9980C396AD56@xxxxxxxxxxxxxxxxxxxx

I have a client (Medical Practice) that requires the "SBS Backup Job" available through the System Manager, to be able to perform the backup using mode "copy" instead of normal as we do not want to reset archive bits. This is because we have in place an 'Offsite / Online' Backup solution that dynamically updates changes to data files in selected folders. I schedule this facility to shutdown for two hours each evening so that the server can do a full system backup, but when I start the offsite facility again, the SBS Backup has changed the archive bits to indicate the files have been backed up, thus the offsite facility will not detect any file changes for that day. How can I modify the automated facility to do a "copy" mode type backup?

Thanks for your Help,

Neil Horley,  
DOTMED – Medilink Consultant  
Burleigh Heads, QLD. Australia  
nhorley@xxxxxxxxxxxxxxxxxxxx

Re: How to Modify Backup Runner to type "Copy" mode