

# Re: TS 2003 – Different Computer policy for different users

---

*Source:*

[http://www.tech-archive.net/Archive/Windows/microsoft.public.windows.terminal\\_services/2009-02/msg00011.html](http://www.tech-archive.net/Archive/Windows/microsoft.public.windows.terminal_services/2009-02/msg00011.html)

---

- *From:* Denis Laskov <[DenisLaskov@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx](mailto:DenisLaskov@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx)>
  - *Date:* Mon, 2 Feb 2009 04:53:01 -0800
- 

Hello Vera  
Great site, thx for link.  
Looks like we going to upgrade.

--  
Best Regards

Denis Laskov  
Arcnet Ltd  
MCSE\MCSA 2003  
CWNA

"Vera Noest [MVP]" wrote:

Check this:

How can I allow only a subset of my users to redirect their local printers and drives?  
[http://ts.veranoest.net/ts\\_faq\\_client\\_resources.htm#multiple\\_listeners](http://ts.veranoest.net/ts_faq_client_resources.htm#multiple_listeners)

---

Vera Noest  
MCSE, CCEA, Microsoft MVP – Terminal Server  
TS troubleshooting: <http://ts.veranoest.net>  
\*----- Please reply in newsgroup -----\*

=?Utf-8?B?RGVuaXMgTGFza292?=  
<[DenisLaskov@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx](mailto:DenisLaskov@xxxxxxxxxxxxxxxxxxxxxxxxxxxxxx)> wrote on 02 feb 2009:

Hi All  
Some strange problem we have – looks like I miss something...  
One terminal server on Win Server 2003 St (TS), few groups of Users. I need to apply different user configuration for Local

## Re: TS 2003 – Different Computer policy for different users

Printer Mapping per user. There is 3 options:

1. Configure this per user (AD – User Properties – Environment)
2. Configure it per TS (In configuration of TS You may configure default behaviour of server in this case)
3. Over Group Policy (Computer Configuration – Windows Components – Terminal Services – Client...)

Its OK and working, but maybe someone know, how may I configure different behaviour for this feature per OU with group policy?

For example – I need user UserA, when it connect to TS, been able to map his local printers to TS, and in the same time user UserB is forbidden to do so, when it connects to the same TS.

And I need to configure it for 40–69 users by OU's, so per–user–manual configuration, unfortunately, is not a good option. Any bright ideas?

thx!